



E1 MINI-PIM

Product Overview

The Juniper Networks single-port E1 Mini-Physical Interface Modules (Mini-PIMs) for the Juniper Networks SSG20 Secure Services Gateway complement the five on-board 10/100 Ethernet interfaces with expanded WAN connectivity.

Product Description

The Juniper Networks[®] E1 Mini-PIMs include one physical E1 port with an integrated channel service unit/data service unit (CSU/DSU). The combination of an E1 modem and an integrated CSU/DSU eliminates the need to deploy several separate external devices, reducing capital expenditures, saving valuable space, and simplifying management

Features and Benefits

- Fully integrated CSU/DSU
- Full and fractional E1 capabilities
- 56K and 64K modes support
- G.703, G.704, and G.706 E1 support
- Independent clock
- Loopback, bit error rate test (BERT), and long build out diagnostics
- Complete configuration and management by command-line interface (CLI), Web user interface, or Juniper Networks Network and Security Manager (NSM)

Specifications

Network Interface Specifications

- Transmit bit rate: 2.048 Mbps
- Receive bit rate: 2.048 Mbps
- Line encoding: HDB3
- Modes: Framed clear channel, unframed clear channel, framed fractional
- Framing: G704, G704 without CRC4, unframed

High-Level Data Link Control (HDLC)

- N x 64 Kbps or N x 56 Kbps, non channelized data rates (E1:N=1 to 31)
- CRC 16/32
- Shared flag
- Idle flag/fill
- Counters: Runts, giants, frame check sequence (FCS), error, abort error, align error

Interface Connector

- RJ-48

Specifications (continued)

System Timing

- External (network recovered clocks)

Dimensions (W x H x D) and Weight

- 3.75 x 0.8 x 5.9 in (9.5 x 2 x 14.5 cm)
- 0.18 lb (81.6 g)

Environmental

- Operating temperature: 0 to 40° C
- Storage temperature: -40 to 70° C
- Relative humidity: 5 to 90% noncondensing

Loopback Diagnostics

- Local, remote, payload
- Test patterns (BERT)
- All ones
- All zeros
- Alternating ones and zeros (AA/55)
- 1:3 or 1 in 4 pattern
- 1:7 or 1 in 8 pattern
- 3:24 - 3 bits set in every 24 bits
- QRSS20 (Modified PRBS 2²⁰-1, with 14 zero suppression)
- PRBS 2⁷-1
- PRBS 2⁹-1 (as specified in ITU-T O.153)
- PRBS 2¹¹-1 (as specified in ITU-T O.153)/2047 pattern
- PRBS 2¹⁵-1 (as specified in ITU-T O.151/O.153)
- PRBS 2²⁰-1 (as specified in ITU-T O.153)
- Programmable word or 32-bit programmable pattern
- Loss of signal (LOS), loss of framing (LOF), alarm indication signal (AIS), yellow alarm (YLW)

Error Counters

- Controlled slipped seconds (CSS or CS)
- Line errored seconds (LES)
- Errored seconds (ES)
- Bursty errored seconds (BES)
- Severely errored seconds (SES)
- Severely errored framing seconds (SEFS)
- Loss of signal seconds (LOS)
- Loss of framing seconds (LOFS)
- UAS unavailable seconds (UAS)

LEDs

PIM LEDs indicate port status with the following LED states:

- Alarm – solid yellow
- Loopback – solid yellow when loopback enabled
- CD (Carrier Detect) – solid green when line is synchronized

Standards and Compliance

Safety

- CAN/CSA-C22.2 No. 60950-1-03/UL 60950-1 Third Edition, Safety of Information

Technology Equipment

- EN 60950-1:2001+A11, Safety of Information Technology Equipment
- IEC 60950-1:2001 First Edition, Safety of Information Technology Equipment

EMC (Emissions)

- FCC Part 15 Class B
- EN 55022 Class B
- AS/NZS 3548 Class B
- VCCI Class B

Immunity

- EN-61000-4-2 ESD
- EN-61000-4-3 Radiated Immunity
- EN-61000-4-4 EFT
- EN-61000-4-5 Surge
- EN-61000-4-6 Low Frequency Common Immunity

European Telecommunications Standardization Institute (ETSI)

- ETSI EN-300386-2: Telecommunication Network Equipment Electromagnetic Compatibility Requirements

Telecom

- TBR12/13
- ACA TS 016

E1 Standards

- ITU-T G.703
- ITU-T G.704
- ITU-T G.706
- ITU-T G.823
- ITU-T G.826

Performance-Enabling Services and Support

Juniper Networks is the leader in performance-enabling services and support, which are designed to accelerate, extend, and optimize your high-performance network. Our services allow you to bring revenue-generating capabilities online faster so you can realize bigger productivity gains, faster rollouts of new business models and ventures, and greater market reach, while generating higher levels of customer satisfaction. At the same time, Juniper Networks ensures operational excellence by optimizing your network to maintain required levels of performance, reliability, and availability. For more details, please visit www.juniper.net/products-services.

Ordering Information

PRODUCT NUMBER	DESCRIPTION
JXM-1E1-S	1-port E1 Mini-Physical Interface Module

The E1 Mini-PIM is supported in ScreenOS 5.4 or greater on the SSG20.


About Juniper Networks

Juniper Networks, Inc. is the leader in high-performance networking. Juniper offers a high-performance network infrastructure that creates a responsive and trusted environment for accelerating the deployment of services and applications over a single network. This fuels high-performance businesses. Additional information can be found at www.juniper.net.



Tel North: 0151 2031400 Tel South: 0118 9071600
Email: info@castleforce.com Web: www.castleforce.com

Copyright 2009 Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, JUNOS, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. "Engineered for the network ahead" and JUNOSe are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

 Printed on recycled paper.