



# V.92 MINI-PIM

## Product Overview

The Juniper Networks single-port V.92 Mini-Physical Interface Module (Mini-PIM) for the Juniper Networks SSG20 Secure Services Gateway complements the five on-board 10/100 Ethernet interfaces with expanded WAN connectivity.

## Product Description

The V.92 modem eliminates the need to deploy several separate external devices, and provides an integrated dial-backup solution that consolidates devices to reduce capital expenditures, save valuable space, and simplify management.

## Features and Benefits

- Cost effective V.92 dial-backup alternative
- On demand dial-backup
- Complete configuration and management by command-line interface (CLI), Web user interface, or Juniper Networks<sup>®</sup> Network and Security Manager (NSM)

## Specifications

### Dimensions (W x H x D) and Weight

- 5.9 x 3.75 x 0.8 in (14.5 x 9.5 x 2 cm)
- 0.17 lb (77.1 g)

### Environmental

- Operating temperature: 0–40° C
- Storage temperature: -40 to 70° C
- Relative humidity: 5 to 90% noncondensing

### LEDs

PIM LEDs indicate port status with the following LED states:

- CD (carrier detect) - Green
- TX/RX - Green

### Network Interface Specifications

- Up to 56 Kbps (V.92)

## Carrier Protocols Supported

- ITU v.92
- K56Flex
- ITUv.23
- Bell 103
- ITU v.21
- ITU v.22
- Bell 212A

## Compression:

- v.42 bis, v.44

## Standards and Compliance

### Safety

- CAN/CSA-C22.2 No. 60950-1-03/UL 60950-1 Third Edition, Safety of Information Technology Equipment
- EN 60950-1:2001+A11, Safety of Information Technology Equipment
- IEC 60950-1:2001 First Edition, Safety of Information Technology Equipment

### EMC (Emissions)

- FCC Part 15 Class B
- EN 55022 Class B
- AS/NZS 3548 Class B
- VCCI Class B

### Immunity

- EN-61000-4-2 ESD
- EN-61000-4-3 Radiated Immunity
- EN-61000-4-4 EFT
- EN-61000-4-5 Surge
- EN-61000-4-6 Low Frequency Common Immunity

## European Telecommunications Standardization Institute (ETSI)

- ETSI EN-300386-2: Telecommunication Network Equipment Electromagnetic Compatibility Requirements

## Telecom

- FCC Part 68/TIA-968
- IC CS-03
- TBR21

## Performance-Enabling Services and Support

Juniper Networks is the leader in performance-enabling services and support, which are designed to accelerate, extend, and optimize your high-performance network. Our services allow you to bring revenue-generating capabilities online faster so you can realize bigger productivity gains, faster rollouts of new business models and ventures, and greater market reach, while generating higher levels of customer satisfaction. At the same time, Juniper Networks ensures operational excellence by optimizing your network to maintain required levels of performance, reliability, and availability. For more details, please visit [www.juniper.net/products-services](http://www.juniper.net/products-services).

## Ordering Information

PRODUCT NUMBER	DESCRIPTION
JXM-1V92-S	1-port v.92 Mini-Physical Interface Module

The V.92 Mini-PIM is supported in ScreenOS 5.4 or later releases on the SSG20.

## About Juniper Networks

Juniper Networks, Inc. is the leader in high-performance networking. Juniper offers a high-performance network infrastructure that creates a responsive and trusted environment for accelerating the deployment of services and applications over a single network. This fuels high-performance businesses. Additional information can be found at [www.juniper.net](http://www.juniper.net).



Tel North: 0151 2031400 Tel South: 0118 9071600

Email: [Info@castleforce.com](mailto:Info@castleforce.com) Web: [www.castleforce.com](http://www.castleforce.com)

Copyright 2009 Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, JUNOS, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. "Engineered for the network ahead" and JUNOSe are trademarks of Juniper Networks, Inc. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.



Printed on recycled paper.